

NEW MODEL OVERVIEW



- iT4 Emission Compliant (HPCR, CEGR, DOC & DPF)
- 21' 4" Straight Boom, 14' 9" Droop Nose Arm
- Cab Riser – 4' Fixed Cab Riser (Std), 6' Fixed Cab Riser (optional), Hydraulic Cab Riser (optional)
- 31.5" (800 mm) Shoes, rollers (2 upper/8 lower)
- 4 Power Modes
- Cooling – Electric Fan Clutch – Hydraulic Oil, Engine Coolant
- Telematics – 3 Year Subscription
- Options – Straight Travel, Diesel Powered Coolant Heater, Cab Guarding, Frame Guard, Catwalk, Additional Work Lamps, Air Compressor, Fuel Filler Pump, Rotating Beacon

NEW MODEL OVERVIEW	DX225MH-3
Rated Power - Gross (HP per SAE J1995)	166 hp (124 kW) @ 1,800 rpm
Operating Weight	60,848 lb. (27,600 kg)
Swing Torque	60,757 lbf.-ft. (8,400 kgf-m)
Drawbar Pull	60,715 lbf. (27,540 kgf)
Max. Loading Reach (@ Pin Point)	35' 5" (10,800 mm)
Max. Loading Height (@ Pin Point)	40' (12,200 mm)
Maximum Auxiliary Hydraulic Flow	2 x 55 gpm (2 x 206.5 L/min)

PL-1002-0414

DOOSAN DELIVERS
equipment for tough jobs